

Outdoor Speed PTZ Dome Camera

HI-PT5618A



Features

- 1/3" CMOS
- High resolution Ex-view 1.3 MP.
- 10X optical zoom, 10X digital zoom.
- True Day/Night, Digital WDR .
- IR distance Up To 60 m , IR Cut Off Filter.
- Day/Night(ICR).
- DNR, Auto iris, Auto focus.
- Pan: 360°endless; Tilt: -3.5° ~30° (Auto Flip)
- Up to 220 presets, auto scan, 8 tour, 4 pattern.
- Ip66 Outdoor Application.
- Auto Flip.
- High Light Compensation (HLC) Function

Accessories (option)



Camera	
Image Sensor	1/3" CMOS
Video Output	1.0V[p-p] / 75Ω, PAL / NTSC composite, BNC
Total Pixel	PAL: 1280 (H)* 960 (V) , NTSC: 1280 (H)* 960 (V)
Focus Mode	Auto / Semiautomatic / Manual
White Balance	Auto / Manual / ATW / Indoor /Outdoor
Minimum Illumination	0.01 Lux At Color / 0 Lux At B/W
S/N Ratio	≥ 50dB (AGC OFF)
Resolutions	Ex-view 1.3 Mega Pixel CMOS
White Balance	ATW / AWC Switchable
Gain Control	AGC ON
Shutter Speed	PAL: 1 ~1/10,000s, NTSC: 1 ~1/10,000s
B.L.C Function	BLC / HLC / DWDR (Digital WDR)
Privacy Mask	8 privacy masks programmable
Focus Model	Auto / Semiautomatic / Manual
IR LEDs	6 pcs IR Array Up To 60mt , IR Cut Filter
Lens	
Zoom Speed	Approx 4.0s(Optical Wide-Tele)
Focal Length	4.9 ~ 49 mm
Angle of View	5.65 ~ 53.2 degree(Wide-Tele)
Pan and Tilt	
Pan / Tilt Range	Pan: 360°endless; Tilt: -3.5° ~30° (Auto Flip)
Pan / Tilt Speed	Pan Manual Speed: 0.6° ~200°/s, Pan Preset Speed: 240°/s
Operating Power	DC 11 ~ 15 V
Number of Preset	256
Patrol I	8 tour up to 32 presets per patrol
Pattern	4 patterns
General	
Protection Level	IP 66
RS-485 Protocols	Pelco-P, Pelco-D, self-adaptive
Working Temperature	-30°C ~65°C (-22°F ~149°F)
Humidity	90% or less
Power consumption	max.20W
Dimensions	Φ245 X 399mm
Weight	Approx. 7.5kg(12.13lbs)