

HI-5404DE (4Video/4Audio) H.264 DVR - FullD1




Features

- H.264 video compression.
- HDMI and VGA output at up to 1920×1080P.
- Dual-stream & Mobile Surveillance.
- Up to 4 -ch synchronous playback.
- Full D1 Video code resolution

Specifications

Analog video input	4PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
Audio input	4PCS RCA Port(Level: 2.0Vp-p, impedance : 1kΩ)
HDMI output	1280*720,1280x1024 1920x1080P
CVBS output	1PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
VGA output	1280*720,1280x1024 1920x1080P
Audio output	1PCS RCA Port(line level , impedance : 1kΩ)
Video compress standard	H.264
Vdideo code resolution	CIF/HD1/D1
Playback resolution	CIF100/120 FPS
Video frame rate	NTSC: 1~30FPS/S; PAL: 1~25FPS/S
Video code rate	256kps/384Kbps/512Kbps/640kpbs/768Kbps/1M/1.5M/2M
Recording Mode	Manual / Timer / Motion / Alarm / Remote
Audio compress standard	ADPCM
Audio code rate	16kpbs
Dual-stream	YES
Synchronously playback channels	1/4 CH
Mode	1*SATA
HDD capacity	support max 4TB HDD
Voice intercom	1PCS RCA Port(Level: 2.0Vp-p, impedance : 1kΩ)
Internet port	1PCS RJ45 10M / 100M adaptive Ethernet Interface
Serial port & PTZ control	1PCS RS485
USB port	2*USB2.0
Alarm input	No
Alarm output	No
Power supply	DC12V
Power consumption(without HDD)	≤10W
Work temperature & humidity	-10℃--+55℃ & Up TO 90%
Weight & Dimensions	0.86kg , 255*215*45 cm

Rear Panel



- 1- Video in
- 2- Video out
- 3- VGA interface
- 4- Audio in
- 5- Network interface
- 6- HDMI interface
- 7- USB interface
- 8- RS-485
- 9- DC12 V



Download APP



iOS



Android