

HI-AHD3404 M (4Port DVR) All In One DVR (Analoge,NVR,AHD)



Features

- H.264 video compression.
- HDMI and VGA output at up to 1920×1080P.
- Dual-stream & Mobile Surveillance.
- Up to 4/8/16-ch synchronous playback.
- Up to 5 Megapixels resolution recording.
- Third-party Hypride Analogue & AHD & Network Camera Supported.

Specifications

Analog video input	4PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
Audio input	4PCS RCA Port(Level : 2.0Vp-p, impedance : 1kΩ)
HDMI output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
CVBS output	NO
VGA output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
Audio output	1PCS RCA Port(line level , impedance : 1kΩ)
Multi-mode switch	AHD: 4CH*720P(compatible with 960H analog) AHD+IP: 2CH*720P+2CH*IPC1080P; IP: 4CH*1080P; 9CH*1080P;
Video compress standard	H.264
Vdideo code resolution	CIF/D1/960H/720P/960P/1080P/3M/5M
Playback resolution	720P 16CH 240/288 FPS+1080P 100/120FPS; 720P 8CH 200/240FPS; (It is defined with the mode switch)
Video frame rate	NTSC: 1~30FPS/S; PAL: 1~25FPS/S
Video code rate	256kps/384Kbps/512Kbps/640Kbps/768Kbps/1M/1.5M/2M/2.5M/3M/4M/5M/6M/8M
Recording Mode	Manual / Timer / Motion / Alarm / Remote
Audio compress standard	ADPCM
Audio code rate	16kpbs
Dual-stream	YES
Synchronously playback channels	1/4 CH
Mode	1*SATA
HDD capacity	support max 4TB HDD
Voice intercom	1PCS RCA Port(Level : 2.0Vp-p, impedance : 1kΩ)
Internet port	1PCS RJ45 10M / 100M adaptive Ethernet Interface
Serial port & PTZ control	1PCS RS485
USB port	2*USB2.0
Alarm input	4 (Not supplied)
Alarm output	1 (Not supplied)
Power supply	DC12V
Power consumption(without HDD)	≤20W
Work temperature & humidity	-10°C-- +55°C & Up T0 90%
Weight & Dimensions	46*37.5*28.5 cm

Rear Panel



- 1- Video in
- 2- VGA interface
- 3- Network interface
- 4- HDMI interface
- 5- USB interface
- 6- Audio in
- 7- Audio out
- 8- RS-485
- 9- DC12 V
- 10- PTZ control