

HI-P20IPC (3MP) IR Fixed Dome Network Camera



Features

- 1/4" CMOS Image Sensor ,3.6 mm Lens.
- High Resolution of 3 M.Pexels.
- HD real-time video.
- Indoor , Poe , WDR .
- IR distance Up To 25 m , IR Cut Off Filter.



Specifications

| | |
|-----------------------|--|
| Image Sensor | 1/4" CMOS. |
| Total Pixel | NTSC: 2048 (H)*1536 (V) PAL: 2048 (H)*1536 (V) |
| ONVIF | Support ONVIF 2.3 |
| IR Cut Off Filter | Yes |
| Minimum Illumination | 0.01 lux@F1.2, AGC ON, 0 lux with IR |
| Protocol | IPv4, IPv6, TCP/IP, IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDN PPOE, P, and 802.1X |
| Resolutions | 3.0 M.Pixels |
| Recording Mode | NVR/CMS/Web |
| Electronic Shutter | NTSC: 1/60 ~1/120,000 sec PAL:1/60 ~1/120,000 sec |
| Wide dynamic range | Digital WDR |
| IR LEDs | 24 pcs ϕ 5mm IR LED |
| Video Output | 1 RJ45 10 M / 100 M Ethernet interface |
| Day / Night | Auto switch |
| IR Distance | 25 mt. |
| Lens | 3.6mm (2.8mm, 6mm, 12mm optional) |
| Operating Power | DC 11 ~ 15 V , 270mA |
| Operating Temperature | -10 C ~ +55 C |
| Operating Humidity | within 95 % RH |
| Color & Material | White & Plastic |
| Weight & Dimensions | 130gm , 84 mm * 62 mm |