

HI-W12IPC (3MP)

IR Fixed Dome Network Camera

Features

- 1/4" CMOS Image Sensor ,3.6 mm Lens.
- High Resolution of 3 M.Pexels.
- HD real-time video.
- Indoor , Poe , WDR .
- IR distance Up To 15 m , IR Cut Off Filter.



Specifications

Image Sensor	1/4" CMOS.
Total Pixel	NTSC: 2048 (H)*1536 (V) PAL: 2048 (H)*1536 (V)
ONVIF	Support ONVIF 2.3
IR Cut Off Filter	Yes
Minimum Illumination	0.01 lux@F1.2, AGC ON, 0 lux with IR
Protocol	IPv4, IPv6, TCP/IP, IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDN PPOE, P, and 802.1X
Resolutions	3.0 M.Pixels
Recording Mode	NVR/CMS/Web
Electronic Shutter	NTSC: 1/60 ~1/120,000 sec PAL:1/60 ~1/120,000 sec
Wide dynamic range	Digital WDR
IR LEDs	15 pcs ϕ 5mm IR LED
Video Output	1 RJ45 10 M / 100 M Ethernet interface
Day / Night	Auto switch
IR Distance	15 mt.
Lens	3.6mm (2.8mm, 6mm, 12mm optional).
Operating Power	DC 11 ~ 15 V , 270mA
Operating Temperature	-10 C ~ +55 C
Operating Humidity	within 95 % RH
Color & Material	White & Metal
Weight & Dimensions	270gm , 94 mm * 69 mm